

ProxCard Plus®

125 kHz Proximity
and Wiegand Swipe

Wiegand Swipe and Proximity Combination Card • Style 16-9



ACCESS reliability.

Application


The ProxCard Plus® combination card offers proximity and Wiegand technologies with optional photo ID capability on a single access control card.

Features

- ▶ Offers universal compatibility with all HID proximity readers.
- ▶ Offers a one-card solution for companies desiring to incorporate a combination of proximity, Wiegand, bar code, magnetic stripe and photo ID technologies for multiple facilities.
- ▶ Ideal for companies transitioning from a Wiegand technology system to an HID proximity-based system.
- ▶ Card thickness is suitable for use with all Wiegand readers and most direct image printers and magnetic stripe readers.

Features

- Proven, Reliable Technology** Offers extremely consistent read range. Unaffected by body shielding or variable environmental conditions, even when close to keys and coins.
- Thin** Can be carried with credit cards in a wallet or purse.
- Photo ID Compatible** Can be directly printed with video image printers and horizontally slot punched for easy use.
- Cross-reference** A cross-reference list correlating the external card number and the programmed ID number is provided for easy system administration. External numbering matching the encoded numbers is available.
- Security** The Wiegand code strip offers over one trillion unique codes. The proximity transponder is programmed to match the Wiegand strip.
- Long Life** Passive, no-battery design allows for an infinite number of reads.
- Durability** Strong, flexible and resistant to cracking and breaking.
- Custom Artwork** Custom multicolor graphics and text are available. Note: custom graphics may increase overall card thickness.
- Warranty** Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).



Specifications

- Typical Maximum* Read Range**
 ProxPoint® Plus reader-up to 1.0" (2.5 cm)
 MiniProx™ reader-up to 2.0" (5.1 cm)
 ThinLine® II reader-up to 1.5" (3.8 cm)
 ProxPro® reader-up to 3.0" (7.6 cm)
 ProxPro® II reader-up to 4.0" (10.2 cm)
 Prox80™ reader-up to 1.5" (3.8 cm)
 MaxiProx® reader-up to 13.0" (33.0 cm)
 EntryProx™ reader-up to 1.0" (2.5 cm)
 pcProx™ reader-up to 1.0" (2.5 cm)
 *Dependent on local installation conditions.

- Code strip layout options**
 A long edge / right side
 AI long edge / left side

- Dimensions**
 2.125" x 3.375" x 0.037" max.
 (5.4 x 8.6 x 0.095 cm)

- Card Construction**
 Thin, vinyl laminate with an internal Wiegand code strip and proximity circuit. An external ABA standard, high coercivity magnetic stripe is optional.

- Operating Temperature**
 -50° to 160° F (-45° to 70° C)

- Weight**
 0.17 oz. (4.8 gm)


- Part Number**
 Style No.: 16-9

- Description**
 125 kHz, plain white finish (front), HID artwork (back), customer-specified ID numbers, location marked for slot punch.

- Options**
 - Card finish for direct printing (glossy or satin)
 - Magnetic stripe
 - External card numbering
 - Slot punch (horizontal or vertical)
 - Custom graphics

(Please see "How to Order Guide" for a description of the options and associated part numbers.)

© 2007 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



MKT-PROXCARD+_DS_EN



ACCESS experience.

hidcorp.com

HID Global Offices:

Corporate North America
 9292 Jeronimo Road
 Irvine, CA 92618-1905
 U.S.A.
 Phone: (800) 237-7769
 Phone: (949) 598-1600
 Fax: (949) 598-1690

Asia Pacific
 19/F 625 King's Road
 North Point
 Island East
 Hong Kong
 Phone: +852 3160-9800
 Fax: +852 3160-4809

Latin America
 Circunvalacion Ote. #201 B
 Despacho 2
 Col. Jardines del Moral
 Leon 37160, Gto.
 Mexico
 Phone: +52 477 779 1492
 Fax: +52 477 779 1493

Europe, Middle East & Africa
 Homefield Road
 Haverhill, Suffolk
 CB9 8QP
 England
 Phone: +44 (0) 1440 714 850
 Fax: +44 (0) 1440 714 840