

L-1 Identity Solutions – Delivering Expertise in Enterprise Access Control

Invest in solutions from the industry leader in biometric access control. Organizations that cannot afford to compromise on security rely on us. We are a pioneer in the use of biometrics for access control and are dedicated to protecting government sites and businesses around the world.

L-1 fingerprint reader solutions combine:

SPEED – Authenticate users in under a second for instantaneous access and high throughput

ACCURACY – Industry leading algorithm ensures secure and dependable authentication

LOW COST OF OWNERSHIP -

Our family of interoperable fingerprint readers reduce the need for costly re-enrollments

PROVEN PERFORMANCE -

Over 290,000 readers deployed worldwide with millions of templates generated. Over 15 years of biometric R&D expertise provides a solid backbone for our innovative solutions

L-1 Fingerprint Reader Solutions Bioscrypt V-Pass FX[™]

Single-factor Fingerprint Authentication

Experience the ultimate in convenience. Eliminate the need for PINs, proximity cards and smart cards to gain access to secure areas. Reduce administrative and human resource costs while quickly providing employees access to restricted areas — it is as simple as the touch of a finger.

Flexible Authentication Options

- Single-factor 1:N identification using just your finger
- Two-factor 1:1 verification when used with an external Wiegand reader
- Capable of authenticating users in under one second
- Duress finger option

Configurable User Base

 Store ~4,000 templates for 1:1 verification or ~500 templates for 1:N identification

Easy Installation & Use

- Plug-and-play installation
- VeriAdmin software for quick and easy initial set-up, template management and device/network configuration
- Self-contained fingerprint unit performs enrollment (via VeriAdmin) and verification
- Flexible communication options support Wiegand formats up to 64 bits
- Works with most standard existing access control systems



SPECIFICATIONS

DIMENSIONS



Depth 2.5" (63.5 mm) RS-232 and RS-485 with pigtail wire connections for COMMUNICATIONS Wiegand IN/OUT USB AUX port ~4,000 templates for 1:1 verification or ~500 templates for 1:N identification; TEMPLATE CAPACITY By default, the V-Pass FX is set to 1:500 mode. The reader must be configured The L-1 Enterprise Access Division manually to run in 1:200 or 1:1 modes. ~350 bytes for 1:1 mode or ~2500 bytes for 1:N mode **TEMPLATE SIZE** Unit supports any 5 Volt based Weigand system supporting 26bit standard STANDARD COMPATIBILITY Weigand format 9 - 24 VDC VOLTAGE CURRENT DRAW Idle: 0.20 amps @ 12 VDC; Max: 0.40 amps @ 12 VDC Flat surface, single-gang or mullion mountable MOUNTING Wall mount plate accepts #6 screws or bolts Trim plate included to cover single-gang box 32° - 140°F (0° - 60°C) **OPERATING TEMPERATURE** Available, contact sales for information OUTDOOR ENCLOSURE Works with VeriAdmin software or BIO-SDK SOFTWARE OPTIONS

ORDERING INFORMATION

| Unit | V-Pass-FX-A,R |
|-----------------|--|
| | ~4,000 templates for 1:1 verification or ~500 templates for 1:N identification |
| Desktop Version | Desktop VF-A,R |
| Demo Kit | Demo VF-A,R |

Length 5.12" (130 mm)

Width 1.97" (50 mm)

Certifications FCC, CE, UL294, cUL, RoHS

All units include wall mounting kit, VeriAdmin software and USB administrator cable

Desktop readers are mounted on a plastic stand and include 120V standard North American power cord

Demo units are mounted on a plastic stand, include storage case and 120V standard North American power cord

Americas

Sales-EnterpriseAccess@L1ID.com 800 444 0496 • 905 940 7490

International

Sales-Intl-EnterpriseAccess@L1ID.com +41 22 849 1051

Offices

Canada • United States • Switzerland

Copyright © 2008, L-1 Identity Solutions, Inc. All rights reserved. The trademarks identified herein are the trademarks or registered trademarks of L-1 Identity Solutions, Inc. or other third party.